



Whisker Pole Size Recommendations

Boat Length:	Working Jib		Genoa	
	Light to Mod. Air	Mod. to Heavy Air	Light to Mod. Air	Mod. to Heavy Air
Up to 16'	ADJ 4'-8'	ADJ 6'-12'	ADJ 6'-12'	HD 6'-12'
Up to 22'	ADJ 6'-12'	HD 6'-12'	HD 6'-12'	LC 8'-14'
Up to 25'	HD 6'-12'	HD 6'-12'	ADJ 7'-15'	ADJ 7'-15'
Up to 28'	ADJ 7'-15'	ADJ 7'-15'	ADJ 7'-15'	LC 10'-18'
Up to 33'	LC 10'-18'	LC 10'-18'	LC 10'-18'	LC 12'-22'
Up to 35'	LC 12'-22'	LC 12'-22'	LC 12'-22'	LC 13'-24'
Up to 46'	LC 13'-24'	LC 13'-24'	LC 13'-24'	LC 15'-27'
Up to 50'	LC 15'-27'	LC 15'-27'	LC 15'-27'	
Custom 50' and Over	Please contact us regarding poles of this size.			



Sailing Services stocks a full range of Forespar® whisker poles, as well as mil. spec aluminum tubing, end fittings, and mast mounting accessories. We will build custom spinnaker poles to your specifications, and assist you with the design of pole lift and storage solutions. Carbon poles are available by special order. Call us for details.

Small Telescoping Poles

Twist lock includes end fittings, and plastic mast pad eye with stainless steel screws.



Part No.	Model No.	Description	List
FOR404000	ADJ 4-8	Telescopes from 53" to 93" /3 lbs.	131.95
FOR404100	ADJ 4-8 DL	With latch fittings on both ends	145.45
FOR406000	ADJ 6-12	Telescopes from 72" to 134" /3 lbs.	180.45
FOR406100	ADJ 6-12 DL	With latch fittings on both ends	191.95

Heavy Duty Telescoping Poles



Heavy duty two-section and three-section aluminum spars can be extended to lengths up to 17' and securely locked into position by an internal twist lock device. Poles feature self-latching Ultra Series fittings on the inboard and outboard ends.

Part No.	Model No.	Description	List
FOR406300	HD 6-12-DL	Telescopes from 79" to 138", 8 lbs.	482.95
FOR407101	ADJ 7-15-DL	Three sections, 83" to 169", 8 lbs.	553.00
FOR304015	HD 6-12 DL	Replacement inboard end fitting for ADJ 6-12	131.45
FOR304018	HD 6-12 DL	Replacement outboard end fitting for ADJ 6-12	131.45
FOR304057	ADJ 7-15 DL	Replacement inboard end fitting for ADJ 7-15	131.45

Tri-Reacher™ Whisker Pole

For boats 35'-42' LOA, the new Tri-Reacher™ whisker pole has been developed specifically for use with Asymmetrical/Gennaker sails. This 3-part telescoping whisker pole used with these sails will allow deeper sailing angles and eliminate the need for constant jibing downwind. Collapses to 8', extends to 21'.



Part No.	Description	SWL	Pole Size	List
FOR408200	Whisker Pole	22 lbs	8' - 21'	1158.00

Aluminum Tubing

Clear anodized to military specification (triple commercial). Prime marine alloy 6063-T6. Tubing sold in stock lengths.

Part No.	O.D.	Length	Wall	I.D.	Wt./Ft.	List
FOR500015	1-1/4"	20'	0.050"	1.150"	.22 lbs.	354.95
FOR500018	1-1/2"	22' 6"	0.065"	1.370"	.35 lbs.	437.95
FOR301005	1-1/2"	7' 6"	0.065"	1.370"	.35 lbs.	149.95
FOR500020	2"	21' 6"	0.065"	1.870"	.47 lbs.	505.00
FOR408003	2"	7' 2"	0.065"	1.870"	.47 lbs.	174.45
FOR401004	2"	9' 1"	0.065"	1.870"	.47 lbs.	210.95
FOR301006	2"	9' 4"	0.065"	1.870"	.47 lbs.	222.95
FOR301058	2-1/2"	20' 2"	0.083"	2.334"	.74 lbs.	727.00
FOR301056	2-1/2"	9'	0.083"	2.334"	.74 lbs.	335.95
FOR301057	2-1/2"	11' 2"	0.083"	2.334"	.74 lbs.	400.95
FOR301065	3"	11' 2"	0.083"	2.835"	1.00 lbs.	488.95
FOR301072	3"	12' 2"	0.083"	2.835"	1.00 lbs.	535.00
FOR301019	3"	13'	0.083"	2.835"	1.00 lbs.	568.00
FOR301063	3"	16'	0.083"	2.835"	1.00 lbs.	697.00
FOR301030	3"	23' 4"	0.083"	2.835"	1.00 lbs.	1,063.00
FOR301061	3-1/2"	24' 4"	0.120"	3.260"	1.50 lbs.	1,574.00
FOR403004	3-1/2"	12' 2"	0.120"	3.260"	1.50 lbs.	602.00
FOR301059	3-1/2"	14'	0.120"	3.260"	1.50 lbs.	908.00
FOR301024	3-1/2"	15'	0.120"	3.260"	1.50 lbs.	967.00
FOR301003	4"	20'	0.120"	3.750"	1.72 lbs.	1,539.00

Line Control™ Whisker Poles

Line Control™ system simplifies the extension and retraction of whisker poles. Just unclench the line to extend or retract. Quick and easy with even the largest poles. Topping lift attachment points are standard on all poles.

Forespar® "Combo" Line Control™ Whisker poles offer all the same features as standard poles, but the Forespar® achieves significant weight savings by using an aluminum outer tube with a carbon fiber inner tube.



Part No.	Model No.	End Fittings	Recommended Mast Fittings	Collapsed Length/Weight	Max. Working Length	Tubing Diameters	List
FOR401106	LC 10-18 EL-UXP	EL-UXP	PE-3SC, RC-125, FC-125	121.75"/17 lbs.	218.13"	2" & 2-1/2"	1,334.00
FOR401107	LC 10-18 EL-UTR	EL-UTR	PE-3SC, RC-125, FC-125	121.75"/17 lbs.	218.13"	2" & 2-1/2"	1,358.00
FOR402200	LC 12-22 UXP-UTR	UXP-UTR	RC-125, FC-125	148.50"/27 lbs.	265.25"	2-1/2" & 3"	1,719.00
FOR402201	LC 12-22 UXP-UTR	UTS-UTR	T-125, AT-125	148.50"/28 lbs.	265.25"	2-1/2" & 3"	2,166.00
FOR800802	LC 12-22 UTS-UTR	CARBON FIBER	T-125, AT-125	148.50"/19 lbs.	265.25"	2-1/2" & 3"	4,399.00
FOR402203	LC 12-22 COMBO	UTS-UTR	T-125, AT-125	148.50"/24 lbs.	265.25"	2-1/2" & 3"	2,928.00
FOR403200	LC 13-24 UXP-UXP	UXP-UXP	RC-125, FC-125	162.00"/38 lbs.	272.00"	3" & 3-1/2"	2,380.00
FOR403202	LC 13-24 UTS-UTR	UTS-UTR	T-125-S	162.00"/39 lbs.	272.00"	3" & 3-1/2"	2,459.00
FOR800800	LC 13-24 UTS-UTR	CARBON FIBER	T-125, AT-125	162.00"/24 lbs.	272.00"	3" & 3-1/2"	5,094.00
FOR403203	LC 13-24 COMBO	UTS-UTR	T-125, AT-125	162.00"/34 lbs.	272.00"	3" & 3-1/2"	3,265.00
FOR405200	LC 15-27 UTS-UXP	UTS-UXP	T-125-S	182.00"/58 lbs.	324.00"	3-1/2" & 4"	3,025.00
FOR405201	LC 15-27 UTS-UTR	UTS-UTR	T-125-S	182.00"/58 lbs.	324.00"	3-1/2" & 4"	3,033.00
FOR800801	LC 15-27 UTS-UTR	CARBON FIBER	T-125, AT-125	182.00"/32 lbs.	324.00"	3-1/2" & 4"	5,784.00
FOR405203	LC 15-27 COMBO	UTS-UTR	T-125, AT-125	182.00"/42 lbs.	324.00"	3-1/2" & 4"	4,358.00



Spinnaker Poles & End Fittings

Small Boat Spinnaker Pole Kits

One end is installed with the other end loose so pole can be cut to desired length and completed in the field. Kits include nylon latching end fittings, nylon lanyard, part eye and hook kit



Part No.	Model No.	O.D.	Max Length	Shipping Weight	List
FOR303600	Mini-6	1"	6'	4 lbs	161.45
FOR303700	Mini-7	1-1/4"	7'	4-1/2 lbs	178.95

Standard Spinnaker Poles

All standard poles are supplied with double bridle topping lift/foreguy system. Unless otherwise specified, all poles are supplied jaws up.

Part No.	O.D.	End Fittings	Max Length	Shipping Weight	List
FOR304100	1-1/2"	UXP - UXP	7' 8"	6 lbs	518.00
FOR304101	2"	UXP - UXP	9' 6"	10 lbs	828.00
FOR304102	2"	UXP - UXP	9' 6"	10 lbs	941.00
FOR304103	2"	UTR - UTR	9' 6"	10 lbs	1,006.00
FOR304104	2-1/2"	UXP - UXP	11' 6"	14 lbs	1,072.00
FOR304105	2-1/2"	UTR - UXP	11' 6"	15 lbs	1,195.00
FOR304106	2-1/2"	UTR - UTR	11' 6"	15 lbs	1,270.00
FOR304107	3"	UXP - UXP	13' 6"	18 lbs	1,352.00
FOR304108	3"	UTR - UXP	13' 6"	19 lbs	1,378.00
FOR304109	3"	UTR - UTR	13' 6"	19 lbs	1,566.00
FOR304110	3-1/2"	UXP - UXP	15' 5"	33 lbs	1,885.00
FOR304111	3-1/2"	UTR - UXR	15' 5"	33 lbs	1,973.00
FOR304112	3-1/2"	UTR - UTR	15' 5"	34 lbs	2,044.00

Offshore Spinnaker Poles

Please specify end-for-end or single topping lift attachment.

Part No.	O.D.	End Fittings	Max Length	Shipping Weight	List
FOR304115	3"	UTS - UTR	13' 5"	18 lbs	1,547.00
FOR304116	3"	UTS - UGPS	13' 5"	19 lbs	2,262.00
FOR304117	3-1/2"	UTS - UTR	15'	33 lbs	2,008.00
FOR304118	3-1/2"	UTS - UGPS	15'	34 lbs	2,824.00
FOR304119	4"	UTS - UGPS	18' 5"	44 lbs	3,315.00
FOR304120	4-1/2"	UTS - UGPS	20' 5"	49 lbs	4,357.00

Carbon Fiber Spinnaker Poles

Forespar® carbon poles are made from pressure-cured intermediate modulus carbon fiber and high performance epoxy resin systems.



Poles come "Jaws Up" with * Double Bridle, or ** Custom Single Bridle.

Part No.	O.D.	End Fittings	Max Length	Weight	List
FOR800901*	2.0"	UXP - UXP	10.0'	4 lbs	Call
FOR800101*	2.5"	UXP - UXP	12.0'	4.5 lbs	Call
FOR800102*	2.5"	UTR - UTR	12.0'	4.5 lbs	Call
FOR800201*	3.0"	UXP - UXP	14.0"	8 lbs	Call
FOR800202*	3.0"	UTR - UTR	14.0"	8 lbs	Call
FOR800203*	3.0"	UTS - UTR	14.0'	9.5 lbs	Call
FOR800301*	3.5"	UTR - UTR	16.5'	11.5 lbs	Call
FOR800302**	3.5"	UXP - UXP	16.5'	11.5 lbs	Call
FOR800303**	3.5"	UTS - UTR	16.5'	12 lbs	Call
FOR800304**	3.5"	UTS - UGPS	16.5'	14 lbs	Call
FOR800404**	4.0"	UTS - GP	18.5'	20 lbs	Call
FOR800405**	4.0"	UTS - UGPS	18.5'	21 lbs	Call
FOR800501**	4.5"	UTS - GP	22.5'	25 lbs	Call
FOR800503**	4.5"	UTS - UGPS	22.5'	26 lbs	Call

Forespar Ultra Series™ End Fittings

Composite end fittings are designed to be durable, high strength, light weight and corrosion resistant. Max. LOA boat outboard end - 43'; Max. LOA boat inboard end - 36'. Spectra™ trip line with terminal eye strap included. All Ultra ends require minimum 1-1/2" inner diameter mast rings. Undersized rings will damage ends and void warranty.

UTR Style - Internal Trip

Part No.	O.D.	I.D.	Length	Weight	List
FOR304060	2.0"	1.870"	2.750"	6.97 oz	187.45
FOR304061	2.5"	2.334"	3.125"	9.25 oz	219.95
FOR304062	3.0"	2.835"	3.000"	11.92 oz	245.95
FOR304063	3.5"	3.260"	3.625"	15.72 oz	301.95



UXP Style - External Trip

Part No.	O.D.	I.D.	Length	Weight	List
FOR304054	1.5"	1.370"	2.750"	6.97 oz	136.95
FOR304050	2.0"	1.870"	1.870"	6.97 oz	150.45
FOR304051	2.5"	2.334"	3.125"	9.25 oz	172.95
FOR304052	3.0"	2.835"	3.000"	11.92 oz	195.95
FOR304053	3.5"	3.260"	3.625"	15.72 oz	273.95



Forespar Offshore Series GP & Ultra Series™ GPS End Fittings

Deluxe ocean racing end fittings featuring a wide flared throat and spring loaded trigger piston. All GP and UGPS fittings are for outboard use only, and will not work with mast cars. Internal trip only.

UGPS Style - Internal Trip

Part No.	O.D.	I.D.	Length	Weight	List
FOR304021	3.0"	2.835"	5.00"	38 oz	594.00
FOR304022	3.5"	3.260"	5.625"	41 oz	698.00
FOR304023	4.0"	3.750"	5.625"	48 oz	729.00
FOR304024	4.5"	4.260"	5.1875"	51 oz	793.00



GP Style - Internal Trip

Part No.	O.D.	I.D.	Length	Weight	List
FOR309030	3.0"	2.835"	5.00"	44 oz	832.00
FOR309033	3.5"	3.260"	5.625"	54 oz	980.00
FOR309035	4.0"	3.750"	5.625"	62 oz	1,025.00
FOR309038	4.5"	4.260"	5.1875"	77 oz	1,113.00



TS & UTS Style - Socket Ends

Part No.	Type	O.D.	I.D.	Weight	List
FOR309028	Aluminum	3.0"	2.835"	26 oz	508.00
FOR304080	Ultra	3.0"	2.835"	20 oz	490.95
FOR309031	Aluminum	3.5"	3.260"	29 oz	545.00
FOR304081	Ultra	3.5"	3.260"	23 oz	509.00
FOR405006	Aluminum	4.0"	3.750"	34 oz	573.00
FOR309036	Aluminum	4.5"	4.260"	45 oz	679.00
FOR304082	Ultra	4.0"	3.750"	23 oz	530.00



Mast Pad-Eyes



Part No.	Description	List
A	FOR400001... Flat base, measures 2-3/4" x 2". 1-5/8" ID	62.45
B	FOR400002... Curved base, measures 2-3/4" x 2". 1-5/8" ID	62.45
C	FOR400012... Flat base, heavy duty, measures 2-3/4" x 2". 1-5/8" ID	74.45
D	RF30... Curved base, fits 2-3/8" dia. masts. 1-3/16" ID	30.53
E	RF41... Curved base, fits 3-1/8" dia. masts. 1-3/4" ID	72.95
F	RF602... Curved base, fits 2-3/8" dia. masts. 1-3/8" ID	33.95